


## AT - Tournevis PROTWIST® pour vis à fente - lames fraisées



### Description :

-

	A [m m]	Diamètre [mm]	Diamètre D1 [mm]	Longueur L1 [mm]	longueur [mm]	Longueur L2 [mm]	Épaisseur [mm]	Largeur [mm]	Poids [g]
<b>AT2.5X50</b>	2.5	19.0	2.5	50.0	144.0	94.0	0.4	2.5	20
<b>AT2.5X75</b>	2.5	19.0	2.5	75.0	169.0	94.0	0.4	2.5	21
<b>AT2.5X75PB</b>	2.5	19.0	2.5	75.0	169.0	94.0	0.4	2.5	21
<b>AT2X75</b>	2.0	19.0	2.0	75.0	169.0	94.0	0.4	2.0	18
<b>AT3.5X100</b>	3.5	25.0	3.5	100.0	203.0	103.0	0.6	3.5	43
<b>AT3.5X100PB</b>	3.5	25.0	3.5	100.0	203.0	103.0	0.6	3.5	43
<b>AT3.5X250</b>	3.5	25.0	3.5	250.0	353.0	103.0	0.6	3.5	55
<b>AT3.5X75</b>	3.5	25.0	3.5	75.0	178.0	103.0	0.6	3.5	41
<b>AT3.5X75PB</b>	3.5	25.0	3.5	75.0	178.0	103.0	0.6	3.5	41
<b>AT3X100</b>	3.0	25.0	3.0	100.0	203.0	94.0	0.5	3.0	33
<b>AT3X75</b>	3.0	19.0	3.0	75.0	178.0	94.0	0.5	3.0	32
<b>AT4X100</b>	4.0	25.0	4.0	100.0	209.0	103.0	0.8	4.0	47
<b>AT4X100PB</b>	4.0	25.0	4.0	100.0	209.0	103.0	0.8	4.0	47
<b>AT4X150</b>	4.0	25.0	4.0	150.0	259.0	103.0	0.8	4.0	52
<b>AT4X200</b>	4.0	25.0	4.0	200.0	309.0	103.0	0.8	4.0	57
<b>AT4X300</b>	4.0	25.0	4.0	300.0	409.0	103.0	0.8	4.0	120
<b>AT5.5X100</b>	5.5	30.0	3.5	100.0	209.0	109.0	1.0	5.5	82
<b>AT5.5X100PB</b>	5.5	30.0	3.5	100.0	209.0	109.0	1.0	5.5	82
<b>AT5.5X125</b>	5.5	30.0	5.5	125.0	234.0	109.0	1.0	5.5	87
<b>AT5.5X150</b>	5.5	30.0	5.5	150.0	259.0	109.0	1.0	5.5	91
<b>AT5.5X150PB</b>	5.5	30.0	5.5	150.0	259.0	109.0	1.0	5.5	91
<b>AT5.5X200</b>	5.5	30.0	5.5	200.0	309.0	109.0	1.0	5.5	105
<b>AT5.5X300</b>	5.5	30.0	5.5	300.0	409.0	109.0	1.0	5.5	130
<b>AT6.5X125</b>	6.5	36.0	6.5	125.0	245.0	120.0	1.2	6.5	132
<b>AT6.5X150</b>	6.5	36.0	6.5	150.0	270.0	120.0	1.2	6.5	140
<b>AT6.5X150PB</b>	6.5	36.0	6.5	150.0	270.0	120.0	1.2	6.5	140
<b>AT6.5X200</b>	6.5	36.0	6.5	200.0	320.0	120.0	1.2	6.5	153
<b>AT6.5X300</b>	6.5	36.0	6.5	300.0	420.0	120.0	1.2	6.5	180

